

ActualtestsQuiz



- ✓ Online Tool, Convenient, easy to study.
- ✓ Instant Online Access
- ✓ Supports All Web Browsers
- ✓ Practice Online Anytime
- ✓ Test History and Performance Review
- ✓ Supports Windows / Mac / Android / iOS, etc.



- ✓ Installable Software Application
- ✓ Simulates Real Exam Environment
- ✓ Builds Exam Confidence
- ✓ Supports MS Operating System
- ✓ Two Modes For Practice
- ✓ Practice Offline Anytime



- ✓ Printable PDF Format
- ✓ Prepared by IT Experts
- ✓ Instant Access to Download
- ✓ Study Anywhere, Anytime
- ✓ 365 Days Free Updates
- ✓ Free PDF Demo Available



Security & Privacy

We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.



365 Days Free Updates

Free update is available within 365 days after your purchase. After 365 days, you will get 50% discounts for updating.



Money Back Guarantee

Full refund if you fail the corresponding exam in 90 days after purchasing. And Free get any another product.



Instant Download

After Payment, our system will send you the products you purchase in mailbox in a minute after payment. If not received within 2 hours, please contact us.

<http://www.actualtestsquiz.com/>

The best test Quiz materials platform for helping you to obtain your dreaming certification as soon as possible.

Exam : E20-816

Title : Symmetrix Solutions Expert Exam
for Technology Architects

Vendors : EMC

Version : DEMO

NO.1 What are the key differences between SIRT in 5772 and SIRT in Symmetrix V-Max with 5874?

- A. SIRT in 5874 is enabled for all write sizes or if RTT > 115 microsec
- B. SIRT in 5874 is enabled for write sizes up to 64 KB or RTT threshold > 520 microsec
- C. SIRT in 5874 is enabled for all write sizes or if RTT < 115 microsec
- D. SIRT in 5874 is enabled for write sizes up to 128 KB or if RTT < 115 microsec

Answer: A

NO.2 An Open Replicator data migration from a HDS to Symmetrix array is being proposed.

The customer

has the following requirements: Application downtime should be minimal and Open Replicator session

failure must not result in data loss

Which solution will meet the customer's requirements?

- A. Cold pull with precopy
- B. Cold pull with donor update
- C. Hot pull with donor update
- D. Hot pull with precopy

Answer: C

NO.3 Click the Calculator icon in the upper left-hand corner.

SRDF/S over Fibre Channel has been configured between two V-Max arrays that are 50 kilometers apart.

What is the expected write response time delay due to latency?

- A. 0.25 ms
- B. 0.5 ms
- C. 1 ms
- D. 2 ms

Answer: C

NO.4 The customer wants a TimeFinder/Snap solution to create a point in time prior to modifying the source

data for testing purposes with a 16-hour RPO.

How should the Change Tracker data collection be set up to model the solution.?

- A. Delta report with a reset of 8 hours
- B. Delta report with a reset of 16 hours
- C. Delta report with a reset of 4 hours
- D. Sum report with a reset of 8 hours

Answer: B

NO.5 The customer has a DMX-4 replicating to another DMX-4 (microcode level 5773 for both) over an SRDF/S session between two sites 20 km apart and wants to understand the limitation (if any) of using the Single Round Trip (SiRT) feature on RF directors. What is the applicable limitation of the setup?

- A. SiRT only works for an I/O size of less than 32 KB.
- B. SiRT is enabled for all block sizes.
- C. SiRT would not work because the distance is greater than 12 km.
- D. SiRT only works for SRDF/A.

Answer: A

NO.6 A customer is migrating their Windows 2008 servers from HP storage to EMC V-Max storage.

Host-based performance metrics need to be used to design a configuration. EMC recommends the

diskperf -Y command to enable I/O statistics in every server.

Why is enabling disk statistics collection recommended?

- A. It improves performance of the servers
- B. Otherwise, a reboot will be required to activate
- C. Otherwise, you must start Performance Monitor
- D. Because Windows 2008 leaves the default value to off

Answer: B

NO.7 A customer is running SRDF/A single session mode. They want to change into SRDF/S mode after

nightly periods of high write activity have completed. The switch to synchronous mode failed.

What is a potential cause for this failure?

- A. SRDF/S cycle switching feature is not enabled.
- B. Mode change feature is only supported with Concurrent SRDF.
- C. SDRF/A write cache is not enabled at the remote site.
- D. Fifty percent or more of SRDF/A write cache is in use on the target Symmetrix.

Answer: D

NO.8 A customer is implementing a new SRDF/S environment with DMX arrays. The primary and secondary

data centers are 20 kilometers apart.

Which consideration is needed for planning, designing, and implementing a synchronous solution?

- A. Ensure that the application can tolerate the additional latency
- B. Ensure that adequate cache on the arrays is allocated
- C. Ensure that the RAID configuration is identical on both arrays
- D. Ensure that there is twice the recommended amount of bandwidth

Answer: A

NO.9 A customer wants to migrate from DMX-3 with 5772 to DMX-4 with 5773 code. They are using

TimeFinder/Clone every night for backup processing with synchronous COFW.

TimeFinder/Clone with

5773 allows them to use a new feature called asynchronous COFW.

How many back-end operations does TimeFinder/Clone make with Enginuity 5773 using Asynchronous

COFW compared with TimeFinder/Clone with Enginuity 5772?

- A. Back-end operations are lower with 5773 Enginuity.
- B. Back-end operations are the same in both Enginuity versions.
- C. Back-end operations are higher with 5773 Enginuity.
- D. Depends on disk speed and RAID protection.

Answer: B

NO.10 A customer is planning to implement SRDF/S into their environment. The customer wants zero data

loss if they lose their primary data center (R1). The distance is 1,000 miles, and the customer would like to

maintain an application response time of 10 ms.

Which design would you implement?

- A. SRDF/AR single-hop
- B. SRDF/AR multi-hop
- C. SRDF/DM
- D. SRDF/S with adaptive copy initially

Answer: B

NO.11 A company has a Symmetrix V-Max array in an open systems environment. They want to use

TimeFinder/Snap to create a single copy per day of a production environment containing 200

volumes of

8 GB each. Twenty-five percent of the total I/O in the application is write activity.

What is the amount of physical storage required for all VDEVs?

- A. 50 GB
- B. 4 GB
- C. 8 GB
- D. 0 GB

Answer: D

NO.12 The customer wants to replace the three DMX 2000s with a single Symmetrix V-Max using Open

Replicator hot pull for the move. What sequence of steps should be taken to get ready for the copy

sessions?

LUN Masking of DMX 2000 remote volumes to the V-Max FA ports.

V-Max and DMX 2000 arrays are reachable via the same fabric or SAN extension.

FA ports of V-Max are zoned to FA ports of the three DMX 2000s.

V-Max and DMX 2000 arrays are reachable via point-to-point or FC-AL.

LUN Masking of the V-Max control volumes to the DMX 2000 FA ports.

All V-Max FAs have access to the DMX 2000 volumes being migrated.

- A. 4,6,1,3
- B. 4,3,5,6
- C. 2,3,1,6
- D. 2,3,5,6

Answer: C

NO.13 The customer wants a TimeFinder/Snap solution to create a point in time prior to modifying the source

data for testing purposes. The snap would be kept for 8 hours. How should the Change Tracker data

collection be set up to model the solution?

- A. Sum report with a reset of 4 hours
- B. Delta report with a reset of 16 hours
- C. Delta report with a reset of 4 hours
- D. Delta report with a reset of 8 hours

Answer: D

NO.14 A customer's application is stored on a DMX-4. The application runs 24x7x365. They

would like to send

consistent replicas of this data simultaneously to four branch offices on a nightly basis. The branch offices have CLARiiON arrays.

Which solution would you recommend?

A. Use TimeFinder/Mirror to create a consistent replica of the production application. Then use Open

Replicator cold push to replicate the data from the BCVs to the remote offices.

B. Use Open Replicator cold push to replicate the data to the remote offices.

C. Use Open Replicator hot push to replicate the data to the remote offices.

D. Use TimeFinder/Snap to create a consistent replica of the production application. Then use Open

Replicator cold push to replicate the data on the VDEVs to the remote offices.

Answer: A

NO.15 A customer has a single V-Max and you are helping to design a new SRDF solution.

This customer

wants to replicate all its data with SRDF over a Gigabit Ethernet.

In order to get the maximum benefit from scaling, what is the most important consideration?

A. All GigE ports on the source should be able to see all GigE ports on the target array

B. Ports must have auto-negotiation off because we don't support Jumbo Frames

C. Speed limit value in the Symmetrix configuration file (not persistent)

D. Speed limits can be set on GigE ports from 100 to 10000 Mb (megabits)

Answer: A